



Stimulated Dynamic Electron Microscopy

Wagner, Jakob Birkedal

Published in:
Proceedings of Microscopy Conference 2015

Publication date:
2015

Document Version
Peer reviewed version

[Link back to DTU Orbit](#)

Citation (APA):
Wagner, J. B. (2015). Stimulated Dynamic Electron Microscopy. In *Proceedings of Microscopy Conference 2015*

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Stimulated Dynamic Electron Microscopy

Jakob B. Wagner

Center for Electron Nanoscopy, Technical University of Denmark, DK-2800 Kgs. Lyngby, Denmark

Monitoring the dynamic nature of nanostructured materials under various stimuli offers the opportunity for studying the dynamic structure-functionality relationship leading to insight and understanding of relevant phenomena for tailor-made materials.

Electron microscopy combined with various stimuli, that being gas exposure, heating, light, biasing, indentation, etc. is a unique tool for such monitoring. Both structural and compositional characterization of materials in active environments are becoming more and more accessible throughout laboratories around the Globe.

Here, a few examples on how stimulated dynamic electron microscopy has shed light on the nature of the nanomaterial dynamics, are discussed - mainly focusing on gas exposure, heat, and visible light treatment.

The redox behavior of nanostructured nickel is of great importance in a variety of applications, including solid oxide fuel cells. Here, the Ni serves as an active part of the anode placed on the fuel side of the cell in form of sub-micron sized grains co-sintered with a ceramic material. During operation at elevated temperature, failure and severe irreversible destruction of the anode will happen due to oxidation of the Ni if exposed to non-reducing conditions. In Fig. 1 the morphological and chemical development of the redox treatment of Ni(O) is shown. The initial NiO agglomerates are reduced in 130 Pa H₂ followed by an oxidation in 320 Pa O₂, both at 600°C. Furthermore, co-sintered Ni-ceramic matrices are treated at similar conditions in the environmental transmission electron microscope (ETEM) in order to elucidate the possible effect of the ceramic on the redox behavior of Ni. [1,2]

Photocatalysts for solar fuel production are subject to intensive investigation as they constitute one viable route for solar energy harvesting. Cuprous oxide (Cu₂O) is a working photocatalyst for hydrogen evolution but it photocorrodes upon light illumination in an aqueous environment. In Fig. 2 the morphological and chemical evolution of Cu₂O cubes are followed by means of ETEM. The presence of H₂O (500 Pa) and visible light (405 nm) results in development of metallic copper grains in the cubes as confirmed by electron energy-loss spectroscopy. The water-light treatment are performed with the electron beam blanked due to electron beam effects. [3]

A few other examples will serve as a teaser for the vast opportunities stimulated electron microscopy in general and environmental transmission electron microscopy in particular gives researchers within the field of energy conversion processes.

- [1] Q. Jeangros, A. Faes, J.B. Wagner, T.W. Hansen, U. Aschauer, J. Van herle, A. Hessler-Wyser, R.E. Dunin-Borkowski, *Acta Materialia* 58 (2010) 4578.
- [2] Q. Jeangros, T.W. Hansen, J.B. Wagner, *Acta Materialia* 67 (2014) 362.
- [3] F. Cavalca, A.B. Laursen, J.B. Wagner, C.D. Damsgaard, I. Chorkendorff, T.W. Hansen, *Chemcatchem* 5 (2013) 2667.




Fig 1: Structural and compositional changes in a set of NiO particles (initial structure shown in (a)) observed after (b) reduction and (c) re-oxidation. The projected areas of (a–c) are superimposed in (d). e) Background-subtracted EEL spectra acquired as a function of temperature for a 4 K min⁻¹ ramp (normalized to unity at L₂). NiO and Ni experimental reference spectra were used to determine the oxidation kinetics (f).




FIG 2: HAADF-STEM images of a Cu₂O nanocube during exposure to H₂O and light. The images show how reduced crystals nucleate and grow within the particle body. STEM EELS on the marked positions is used to investigate the chemical phase of individual grains. The plot shows that a predominantly reduced phase at position 1 and an oxidized phase at position 2 coexist in the particle after 45 min exposure. Scale bar 50nm.